

## Teste di avvitatura

### *Screwing Heads*



Da circa vent'anni la **MIBA** realizza per il mercato italiano ed estero ogni tipo di testa di avvitatura.

Hold&Drive, in linea oppure ad angolo con testa aperta o chiusa le testine d'avvitatura MIBA possono raggiungere range di coppia da un minimo di 5Nm fino ad un massimo di 2000Nm.

Tutte le teste a rinvio d'ingranaggio MIBA sono progettate, prodotte, assemblate e testate presso il nostro sito produttivo di Orbassano (TO).

Soluzioni *speciali* possono essere realizzate su espressa richiesta del cliente.

*For nearly twenty years, the MIBA realizes for the Italian and foreign market all head tightening.*

*Hold & Drive, in line or at an angle with open or closed head, the MIBA screwing heads can reach torque range from a minimum of 5 Nm up to a maximum of 2000 Nm.*

*All MIBA Idle gear heads are designed, manufactured, assembled and tested at our production site in Orbassano (TO).*

*Special solutions could be implemented on customer request.*

Tel : (+39) 011.90.63.005  
 Fax : (+39) 011.90.16.462  
 E-mail : [miba@mibaexpert.com](mailto:miba@mibaexpert.com)  
 Web Site : [www.mibaexpert.com](http://www.mibaexpert.com)

MIBA S.R.L.  
 Via San Luigi, 13 / B  
 10043 ORBASSANO (TO) ITALY



CERT. N.50 100 3645



T99 CH36		Testa in linea: coppia 1500 N/m <i>In line head: torque 1500 N/m</i>
T127		Testa in linea aperta: coppia 20 N/m <i>Open in line head : torque 20 N/m</i>
T157 CH10 HOLD AND DRIVE		Testa Hold & Drive : coppia 60 N/m <i>Head Hold&amp;Drive: torque 60 N/m</i>
T173000 IN LINEA  T173000 IN LINE		Testa in linea aperta: coppia 20 N/m <i>Open in line head: torque 20 N/m</i>
TESTE DI AVVITATURA		
THP 165		
THP 348000		
EPINGLEUSE		Testa multipla per avvicinamento dadi mozzo ruota <i>Multiple head to approach the wheel hub nuts</i>



MIBA s.r.l. Cap. Sociale € 26.000,00 int. vers.  
 Partita IVA 04631440015

C.C.I.A.A. 647105  
 Trib. Pinerolo reg. soc. 2594/8

